




NTN BEARING CORP.OF AMERICA



0.787 Inch | 20 Millimeter x 2.047 Inch | 52 Millimeter x 0.591 Inch | 15 Millimeter NTN NU304EG1C3 Cylindrical Roller Bearings

Bearing No. NU304EG1C3

NU304EG1C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0.157
EAN	4547359145250
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	20MM Bore; Straight Bore Profile; 52MM Outside Diameter; 15MM Width;



NTN BEARING CORP.OF AMERICA

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Intern
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	NU304EG1C3
Weight / LBS	0.347
d	0.787 Inch 20 Millimeter
D	2.047 Inch 52 Millimeter
B	0.591 Inch 15 Millimeter
bore diameter:	20 mm
precision rating:	ISO Class 0
outside diameter:	52 mm
maximum rpm:	11000 rpm
overall width:	15 mm
bearing material:	Hardened Alloy Steel
flanges:	(2) Outer Ring
cage material:	High Strength Machined Brass Rivetless w/ square holes
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
outer ring width:	15 mm
ring separation:	Separable Inner Ring
fillet radius:	1 mm



NTN BEARING CORP.OF AMERICA

operating temperature range:	-40 to 120 ° C
series:	NU
dynamic load capacity:	31500 N
manufacturer product page:	Click here
static load capacity:	26900 N